

LED Sensor Panel Series 4

SPECIFICATIONS

VOLTAGE	220-240AC
POWER FACTOR	>0.90
CRI	>80
IP RATING	IP20
BEAM ANGLE	110°
INSTALL ACCESSORIES	Surface Mount Kit Recessed Frame Suspension Kit

Occupancy and Daylight built in Microwave Sensor:

MOUNTING HEIGHT	3.5m
DETECTION RANGE	8m Diameter
DAYLIGHT THRESHOLD	450 Lux
MOTION HOLD	20mins
STANDBY	30% dim
ACCESSORIES	Remote Control



ILUMINOUS MODELS

MODEL	POWER	LCP	LUMEN	DIMENSIONS	CCT
PPAN14W3X123KFS	14w	13.45w	2300	294*1194*30mm	3000K
PPAN14W3X124KFS					4000K
PPAN14W3X125KFS					5000K
PPAN14W3X126KFS					6000K
PPAN20W3X123KFS	20w	19.21w	3300	294*1194*30mm	3000K
PPAN20W3X124KFS					4000K
PPAN20W3X125KFS					5000K
PPAN20W3X126KFS					6000K
PPAN14W6X63KFS	14w	13.49w	2300	594*594*30mm	3000K
PPAN14W6X64KFS					4000K
PPAN14W6X65KFS					5000K
PPAN14W6X66KFS					6000K
PPAN20W6X63KFS	20w	19.28w	3300	594*594*30mm	3000K
PPAN20W6X64KFS					4000K
PPAN20W6X65KFS					5000K
PPAN20W6X66KFS					6000K

GET IN TOUCH

 info@primsal.com

 primsal.com